



Zeutschel OS Q0

The scanner for highest demands up to DIN A0+





Zeutschel OS Q0

The new dimension of scanning

The OS Q0 Scanner generation is the result of new technological developments as well as our consistent work on technical innovations. It fulfills the highest demands under the headings of image quality, process efficiency and productivity.

The unique image quality of the OS Q0 is based on the perfect interplay of especially highquality technical components. Thus, the image quality of the OS Q0 extends far beyond the requirements of all common digitisation standards, e.g. ISO 19264-1, Metamorfoze or FADGI. The scanning system features a completely new and self-developed camera system with a CMOS-based line sensor. The camera features a high dynamic range and is also capable of reproducing the finest gradations. The result: sharp, low-noise, high-contrast images which reflect even the finest details true to the original. A special guided lighting of the LED lighting system with a constant angle enables the OS Q0 to reproduce even difficult originals free from reflection or shadowing. Reflections on shining surfaces or shadows in the book fold are optically corrected.

A CRI value of over 97 combined with optimally matched camera and lighting components enable excellent colour rendering. The OS Q0 sets the reference mark for high scanning productivity. The OS Q0 Scanner series achieves the highest efficiency in the scanning process through the perfect interplay with tried and tested Zeutschel imaging systems. Functions such as self-opening glass panes, sliding self-balancing book supporting plates and a scanning automatic system ensure the highest productivity levels. The OS Q0 Overhead Scanner is designed as a flexible modular system. If the requirements and tasks increase, it can be expanded in a modular way. Part of the standard equipment is an optical zoom for imaging smaller format documents.



Options and Accessories



Bookholder on Copyboard
OT 180 H 35 XL700



Kit 90°



Toplight Table AT 0 with
opened glass plate



LED lighting system
for reflection free &
shadow free results



1. Camera system
with a CMOS-based
line sensor
2. Optical Zoom



Wide range of
interchangeable
imaging systems



Compliant to
ISO 19264-1 Level A
FADGI 4 Star
Metamorfoze Full

The Advantages at a Glance

- RGB line sensor (3-channel, CMOS technology)
- Resolution of up to 600 ppi
- Fulfils ISO 19264-1 Level A, Metamorfoze Full und FADGI 4 Star
- Internal image processing with 96 bit
- Data output in 48 bit/24 bit colour, 16 bit/8 bit grayscale and 1 bit b/w
- True RGB capture on each pixel (no colour interpolation)
- Colour rendering index (CRI) of LED lighting >97
- True parallel scanning
- Camera Link interface for fastest image transfer
- Optical Zoom
- Variable lighting times and aperture settings
- OmniScan software with 48 bit data output
- Focused line lighting for glare-free operation
- Fastest scanning speed
- Perfect Book – 3D scan technology for perfect book curve correction
- Parallel scanning and saving process based on 64 bit technology & multi-threading
- Bi-directional scanning
- No UV/IR radiation

- Colour rendering corresponds to the original.

- No reflections with high-shine originals

- Ergonomic work method with or without glass plate

- High productivity based on ROI scan function
(limitation of the area to be scanned)

Made in Germany

Climate Neutral Production

Sustainable Materials



Technical Data

OS Q0

Input and Camera	
Camera sensor	RGB line sensor (3-channel, CMOS technology)
Resolution	MeanMTF10 at 600 ppi: 6,3 LP/mm (with max. zoom-in up to 12 LP/mm)
Camera system	wear-free mechanical shutter, variable exposure time, electronically adjustable aperture; automatic white and black balance, variable depth of focus
Max. original size	>DIN A0, depending on book cradle
Max. book thickness	with book cradle OT 180 H A0 – 220 mm with book cradle OT 180 H 35 XL700 – 350 mm with book cradle OT 180 H 50 XL – 500 mm
Scan mode	96 bit color
Scanning speed in A0 (from start to end of scanning process)	200 ppi – 5 sec. 400 ppi – 7 sec. 600 ppi – 10 sec.
Scanner interface	Camera Link
Zoom	A0 – A2
Electrical data / safety	
Voltage	110 – 240 V
Frequency	50 – 60 Hz
Max. consumption	440 W
Safety inspections / authorizations	
Authorization in accordance with the IEC agreement	international authorization for the safety of IT products – includes EMC, electrical safety, device safety for CE, UL, ETL, CSA
LEDs tested in accordance with	IEC 62471:2006 "Photobiological safety of lamps and lamp systems"
Dimensions	
Width [mm]	1730
Depth (scanner including imaging system) [mm]	3000
Height [mm]	2200
Copyboard Systems	A0: OT 180 H A0, AT 0, Vacuum table A0 A1: OT 180 H50 XL, OT 180 H 35 XL700, OT 180 H, OT 180, AT 1, OT 90, Vacuum table
Accessories for imaging systems	Kit 90°, bookend 110° – 140°
Recommended working conditions	Temperature range: 18 – 35°C Relative air humidity, non-condensing: 80 %
Operating system	
Operating system	Windows 10 (64 Bit) – from OS 12.14 Windows 11
Scanning software	min. OmniScan 12.12 64 Bit

Get in touch



(024) 7625 4955




www.genus.uk



info@genus.uk



Hammond Close, Attleborough Fields
Industrial Est, Nuneaton, Warwickshire,
CV11 6RY, UK



- Digitisation Solutions
- Scanning & Capture Services
- Document, Book & Microfilm Scanners



- Microfilm Solutions
- Fujifilm
- Conversion Services
- Conversion Hardware



- Technical Support
- Hardware Support
- Software Support



- Content Management
- Electronic Document Management
- Digital Asset Management



- Print Solutions
- Design & Print
- Web